



山美

Magnetic Separator



Magnetic Separator

RCYB Series Manual-Cleaning Permanent Magnetic Separator.
RCYD Series Belt Permanent Magnetic Separator.

RCYB Series Manual-Cleaning Permanent Magnetic Separator

Applicable Scope: Remove iron in non-magnetic materials on belt conveyor, vibrating feeder and blanking chute.



Technical Data

Model	Adaptive Belt Width(mm)	Suspension Height(mm)	Belt Velocity(m/s)	Material Thickness(mm)	Weight(kg)	Overall Dimensions (L×W×H)mm		
RCYB-5	500	150	4.5	90	260	500	350	260
RCYB-6.5	650	200	4.5	150	300	650	600	300
RCYB-8	800	250	4.5	200	380	950	950	380
RCYB-10	1000	300	4.5	250	380	1180	1100	380
RCYB-12	1200	350	4.5	300	420	1300	1340	420
RCYB-14	1400	400	4.5	350	420	2350	1500	420

RCYD Series Belt Permanent Magnetic Separator

Applicable Scope: It is used together with belt conveyor, vibrating feeder and so on; applicable to automatic removal of 0.1-35kg ferro-magnetic materials from moving materials, and extensively applied in cement, metallurgy, mine, glass, coal and other industries.



Technical Data

Model	Adaptive Belt Width(mm)	Suspension Height(mm)	Belt Velocity(m/s)	Material Thickness(mm)	Weight(kg)	Overall Dimensions (L×W×H)mm			Motor Power(kw)
RCYD-5	500	150	4.5	80	750	1900	735	935	1.5
RCYD-6.5	650	200	4.5	150	1200	2165	780	1080	2.2
RCYD-8	800	250	4.5	200	1400	2350	796	1280	2.2
RCYD-10	1000	300	4.5	250	2120	2660	920	1550	3.0
RCYD-12	1200	350	4.5	300	3350	2900	970	1720	4.0
RCYD-14	1400	400	4.5	350	4450	3225	1050	1980	4.0

SHANGHAI SANME MINING MACHINERY CO.,LTD (Jv with HAZEMAG, Germany)

Head Office

Tel: +86 21 58202968 +86 21 58206909

Fax: +86 21 58200089

Email: sales@sanmecrusher.com

Address: No.899 Dongfang Road, Pudong New District 200122, Shanghai, China